


You have purchased the Connect™ software (formerly named ECB) solution. Setup of this software involves three components to be completed before you can take advantage of its features: software installation/configuration, network setup/configuration, and device connection/registration.

The device connection/registration must be completed last and can be completed by the product installer if the other preparation steps below are completed prior to the installation of the product on the vehicles.

Preparation for the Hardware Installation

Your IT professional must complete the steps below in preparation for the product installer:

1. Software Setup:
 - a. Install the Connect™ server application (PV Transfer) on the computer/server per the instruction guide.
 - b. Start the server application Windows service.
 - c. Enable Device Registration Auto-Approval (Default) in the software security settings to allow new devices to automatically be approved.
 - d. Write the Server URL from the server application below.



2. Wi-Fi Connection
 - a. Setup at least one Wi-Fi Access Point (AP) with adequate coverage of the vehicle parking area.
 - b. Configure an SSID on the AP with name/password that meets the requirements.
 - c. Write the Wi-Fi SSID Name and Wi-Fi Password below
 - d. Use a laptop or device with Wi-Fi and connect to the SSID from the location the vehicles will be parked.
 - e. Open a web browser on the device and enter the Server URL, if the “PV Transfer” web page opens successfully it confirms that the server is accessible; devices can now be connected.

Wi-Fi SSID Name	
Wi-Fi Password	
Server URL	

The Wi-Fi AP and SSID must meet the network requirements in the Connect™ Software Overview document. If the requirements are not met, the installer may not be able to complete the setup. The document is available at the link below:
<http://files.provisionusa.com/guides/ConnectSoftwareOverview.pdf>

Installation

The installation technician will complete the steps following below to connect the devices to the software:

1. Install the DVR unit(s) and the vehicle Wi-Fi antennas required for connectivity.
2. Enable the DVR unit’s Wi-Fi Client and connect it to the Wi-Fi AP using the SSID and Password provided above.
3. Enable File Transfer and set the Server URL to the address provided above.
4. Confirm the device is registered and approved on the server successfully.